

**Informations à fournir à la commande – Ordering Data**

<input type="checkbox"/> UFM-M	<input type="checkbox"/> UFM-R	<input type="checkbox"/> <b>DTMR32</b>	<input type="checkbox"/> DTMR33
<input type="checkbox"/> UFM-M/1S10	<input type="checkbox"/> UFM-R /1S10	<input type="checkbox"/> <b>DTMR32/1S10</b>	<input type="checkbox"/> DTMR33/1S10
<input type="checkbox"/> UFM-M/14DI	<input type="checkbox"/> UFM-R /14DI	<input type="checkbox"/> <b>DTMR32/14DI</b>	<input type="checkbox"/> DTMR33/14DI
<input type="checkbox"/> UFM-M/14DO	<input type="checkbox"/> UFM-R /14DO	<input type="checkbox"/> <b>DTMR32/14DO</b>	<input type="checkbox"/> DTMR33/14DO
<input type="checkbox"/> UFM-M/3S20	<input type="checkbox"/> UFM-R /3S20	<input type="checkbox"/> <b>DTMR32/3S20</b>	<input type="checkbox"/> DTMR33/3S20

UML-ES  
 UML-ES/1S10  
 UML-ES/14DI  
 UML-ES/14DO  
 UML-ES/3S20

**Source auxiliaire – Auxiliary supply**

Type 1 : 24...110 Vac – 24...125 Vdc +/-20%  
 Type 2 : 80...220 Vac – 90...250 Vdc +/-20%  
 PSU : 90...125 Vdc/Vac – +/-20% (**14DO et 3S20**)

**Montage – Execution**

Encastré – Flush mounting  
 En saillie – Surface mounting  
 Rack 19" 3U – Standard rack 19"3U

**Configuration – Configuration**

Entrées logiques – *Digital inputs (14DI – 1S10 et 3S20)*

48Vdc  
 110 Vdc  
 125Vdc  
 ajout – *additional D8+D16 (14DI et 3S20)*

Relais de sortie – *Output relays (14DO et 3S20)*

R12 : 2\*NO  
 R13 : 2\*NO

**Calibre nominal – Rated input**

unité phases – phase unit

In = 1A  
 In = 5A  
 Un = 50 – 150V

unité homopolaire – zero sequence unit

Ion = 1A  
 Ion = 5A

**Communication - Protocol**

Modbus RTU/ IEC 61-870  
 Modbus TCP/IP  
 IEC 61-850

**Demande spéciale – Special request**

**Quantité - Quantity** \_\_\_\_\_

