

**Informations à fournir à la commande – Ordering Data**

<input type="checkbox"/> UFM-M	<input checked="" type="checkbox"/> <b>UM-RAV</b>	<input type="checkbox"/> DTMR32	<input type="checkbox"/> DTMR33
<input type="checkbox"/> UFM-M/1S10	<input checked="" type="checkbox"/> <b>UM-RAV/1S10</b>	<input type="checkbox"/> DTMR32/1S10	<input type="checkbox"/> DTMR33/1S10
<input type="checkbox"/> UFM-M/14DI	<input checked="" type="checkbox"/> <b>UM-RAV/14DI</b>	<input type="checkbox"/> DTMR32/14DI	<input type="checkbox"/> DTMR33/14DI
<input type="checkbox"/> UFM-M/14DO	<input checked="" type="checkbox"/> <b>UM-RAV/14DO</b>	<input type="checkbox"/> DTMR32/14DO	<input type="checkbox"/> DTMR33/14DO
<input type="checkbox"/> UFM-M/3S20	<input checked="" type="checkbox"/> <b>UM-RAV/3S20</b>	<input type="checkbox"/> DTMR32/3S20	<input type="checkbox"/> DTMR33/3S20

- UML-ES
- UML-ES/1S10
- UML-ES/14DI
- UML-ES/14DO
- UML-ES/3S20

**Source auxiliaire – Auxiliary supply**

- Type 1 : 24...110 Vac – 24...125 Vdc +/-20%
- Type 2 : 80...220 Vac – 90...250 Vdc +/-20%
- PSU : 90...125 Vdc/Vac +/-20% **(14DO et 3S20)**

**Montage – Execution**

- Encastré – Flush mounting
- En saillie – Surface mounting
- Rack 19" 3U – Standard rack 19"3U

**Configuration – Configuration****Entrées logiques – Digital inputs (14DI – 1S10 et 3S20)**

- 48Vdc
- 110 Vdc
- 125Vdc
- ajout – additional D8+D16 **(14DI et 3S20)**

**Relais de sortie – Output relays (14DO et 3S20)**

- R12 : 2\*NO
- R13 : 2\*NO

**Calibre nominal – Rated input**

unité phases – phase unit

- In = 1A
- In = 5A
- Un = 50 – 150V

unité homopolaire – zero sequence unit

- Ion = 1A
- Ion = 5A

**Communication - Protocol**

- Modbus RTU/ IEC 61-870
- Modbus TCP/IP

**Demande spéciale – Special request****Quantité - Quantity** \_\_\_\_\_