

ELR-4o / ELR-m4o ELR-4v / ELR-m4v

EARTH LEAKAGE RELAY
FLUSH MOUNTING VERSIONS DIN 48X96 mm

MICROENER

GENERALITY



The ELR-4 and ELRm-4 series, maintain all the basic characteristics of the DIN 96x96 mm. series, although their reduced dimensions.

An outstanding characteristic of the present relays, is the permanent control of the Toroidal - ELR circuit.

Its interruption brings along the immediate trip of the protection. This allows to identify the anomaly, without waiting to the periodical control, made with the Test push button.

The instrument , fitted with filters at the input circuits, is practically immune to external disturbances, so as the pulse currents with dc components, complying with the requirements of VDE 0664 and project IEC 23 Standards.

MODELS

ELR-4v / ELR-m4v ELR-4o / ELR-m4o	110Vac/dc - 230 - 400 Vac
--------------------------------------	---------------------------

ELR-4v / ELR-m4v ELR-4o / ELR-m4o	24-48 Vac/dc
--------------------------------------	--------------

OPTIONS

F	built - in filter for 3rd harmonic
T	tropicalisation


Following versions available:

DIN 96x48 mm ELR-40 and ELR-m40

DIN 48x96 mm ELR-4V and ELR-m4V

With reduced depth of 75 mm.

LEGEND




1	Tripping time delay setting potentiometer
2	Tripping current setting potentiometer
3	Constant selection micro switch: • a Automatic reset with micro (a) in position 1 • b Constant selection for time settings: K = 1 for micro(b) in position 0; K=10 for micro (b) in position 1; • c Constant selection for current settings: K=0,1 for micros (c-d) in position 0; K= 1 for micro (c) in position 1 and (d) in position 0; K=10 for micro (c) in position 1 and micro (d) in position 1.
4	Test push button.
5	Manual reset push button.
6	Signalling lamp for Aux. Supply presence (green LED)
7	Signalling lamp for relay tripped (red LED)
8	Mechanical Signalling (only for ELRm)

ELECTRICAL CHARACTERISTICS

models and value	ELR- 40	ELR-m40	ELR-4V	ELR-mV
Auxiliary Voltage supply	24-48V ac/dc	110Vac/dc - 230 - 400 Vac ±20% (standard)		
Frequency		50 ÷ 60 Hz		
Maximum consumption		4 VA		
Current tripping setting range $I_{\Delta N}$	0,025÷0,25A K=0,1 - 0,25÷2,5A K=1 - 2,5÷25A K=10 25÷250A*			
Tripping time setting range t		0,02÷0,5 sec K=1 - 0,2÷5 sec K=10		
Mechanical Signalisation	-	•	-	•
Output: 2 changeover contacts		5A 250V		
Working Temperature		-10 + 60°C		
Storing Temperature		-20 + 80°C		
Relative humidity		90%		
Insulation Test		2,5 kV 60 sec.		
Standards	CEI 41-1/IEC 255/VDE 0664/IEC 755/CEI 64.8/ EN 61008-1(1999-11)/EN 62020 (1999-09) / EN 61543 (1996-09) /EN61326-1(1998-04) / EN 61326/A1 (1999-05)-IEC 60947-2 ANNEX M			
Wiring method		Screw terminals for cross section wires 2,5 mm²		
Protection degree according DIN 40050		IP 20		
Frontal protection degree		Ip52 (opt. IP54)		

* By means of an external multiplier (see pag. 40)

WIRING DIAGRAM - LEGEND



LEGENDA

0-3 = 400 V ac
0-2 = 230 V ac
0-1 = 110 V ac/dc

0-2 = 48 V ac/dc
0-1 = 24 V ac/dc

DIMENSIONS

